


GENERAL NOTES:



Onduline Roofing Sheet

Length	Width	Surface Area	Thickness	Width of Corrugation	Height of Corrugation	No. of Corrugation	Weight	Color
950mm	2000mm	1.9 sqm	3mm	95mm	38mm	10	3.4kg/m ²	Red, Brown, Green, Black

Membrane cover

BLACK EPDM Rubber Roofing / Waterproofing Membrane, 1.15 mm thick, 6m Wide, Roll-Folded for Shipment, Class-A Fire and Energy Star Rated. 15 Year Factory Warranty.

Or- Spritech 400 2S (Durable heavy-duty underlay system with grid reinforcement-Superior abrasion and tear resistance)

A heavy-duty underlay with a unique glue strip system that provides raintight overlap and passes the BS 5534:2014 wind uplift requirements for use anywhere in the UK. This is ideal for both warm and hybrid roof systems where wind penetration can affect the performance of the roof insulation at rafter level, as well as traditional cold roofs where the underlay needs to effectively withstand the wind uplift forces acting upon it to ensure it reduces wind loading of the roof tiles.

REVISIONS

NO.	DATE	DESCRIPTION	BY

PROJECT:

CLIENT NAME:
ITALIAN AGENCY FOR DEVELOPMENT
COOPERATION (AISC)

LOCATION:
Ain Zhalta

PLOT NO:

DRWG. TITLE:

Wooden Cabin
Material Specifications

SCALE: DWG. NO. 4

Date: SHEET NO. 5

CIVIL ENGINEER
Wael Bahjat Halawi

DESIGN
STUDY
EXECUTION
SUPERVISION

Shouf Cedar Reserve
Tel: +961 81 718 398
+961 5 350250/114
e-mail: wael@shoufcedar.org